



GE SERIES

Multi-heads automatic embroidery machines | Foshan Factory |

Better **Performance,**
Better **Availability !**



SUNSTAR CO., LTD.

Head office #178-67, GAJWA-DONG, SEO-GU, INCHEON, KOREA

tel +82[0]32-580-5980-93 fax +82[0]32-579-8350-51 www.swfkorea.com





For W24 service
www.swf-service.com



SWF	/	GE	-	W	D	9	20	-	55
Series		M/C Type			Head Interval		Y-Stroke		
							No. of Heads		
							No. of Colors		

Specifications		
Speed		Max. 900 rpm [SQ 800 rpm]
Stitching Length		0.1 ~ 12.7 mm
Motor	Main	Servo Motor x 1
	X-Y	Pulse Motor x 2
Electricity		1-Phase 200V, 220V, 240V [50/60Hz]
		3-Phase 200V, 220V, 240V, 350V, 380V, 415V [50/60Hz]
Power Consumption		1.5 kW
Bobbin Winder		Standard
Upper Thread Holding Unit		Standard
Operation Box		Standard : Color LCD Screen
Hook		Standard Hook
Memory Capacity		Standard : 3,500,000 stitches
Memory Media		USB Memory Stick
Safety Device		Standard : Emergency Stop, Error Code Message
Optional Device		SQ30/SQ31D, SQ35, Cording, Boring

Division of Model										
Model	Head Interval [mm]	Color	Head	Y-Stroke [mm]	Alternative	Emb. Space [mm]		Machine Size [mm]		
						Each Head	All Head	Length	Width	Height
GE-WD920-55	300	9	20	550	non alternative	300 x 550	6,000 x 550	7,333	1,548	1,503
GE-WD(X)921-120	300[600]	9	21	1,200	alternative	300[600] x 1,200	6,300 x 1,200	7,935	2,880	1,503
GE-WE912-55	330	9	12	550	non alternative	330 x 550	3,960 x 550	5,323	1,548	1,503
GE-WE920-55	330	9	20	550	non alternative	330 x 550	6,600 x 550	7,963	1,548	1,503
GE-WE920-75	330	9	20	750	non alternative	330 x 750	6,600 x 750	7,963	1,950	1,503
GE-WE920-120	330	9	20	1,200	non alternative	330 x 1,200	6,600 x 1,200	7,973	2,879.5	1,503
GE-WE(BX)920-130	330[660]	9	20	1,300	alternative	330[660] x 1,300	6,600 x 1,300	8,683	3,079	1,503
GE-WE(X)922-120	330[660]	9	22	1,200	alternative	330[660] x 1,200	7,260 x 1,200	9,013	2,880	1,503
GE-WH912-75	400	9	12	750	non alternative	400 x 750	4,800 x 750	6,233	1,948	1,503
GE-WH918-75	400	9	18	750	non alternative	400 x 750	7,200 x 750	8,633	1,948	1,503
GE-WH918-100	400	9	18	1,000	non alternative	400 x 1,000	7,200 x 1,000	8,633	2,479	1,503
GE-WH(BX)913-130	400[800]	9	13	1,300	alternative	400[800] x 1,300	5,200 x 1,300	7,495	3,080	1,503
GE-WH(BX)915-130	400[800]	9	15	1,300	alternative	400[800] x 1,300	6,000 x 1,300	8,293	3,080	1,503
GE-WH(BX)918-130	400[800]	9	18	1,300	alternative	400[800] x 1,300	7,200 x 1,300	9,493	3,080	1,503
GE-WH(X)906-75	400[800]	9	6	750	alternative	400[800] x 750	2,400 x 750	4,030	1,930.5	1,503
GE-WG909-75	800	9	9	750	non alternative	800 x 750	7,200 x 750	9,085	1,948	1,503

Optional Device			
			
SQ30	SQ31D	Cording	Boring